SKFT1000NS-A

Two Solid Door Freezer, Unlit Sign, with Internal Lighting

Range: ActiveCore Freezer
SKOPE ID: LT10SBN
Dimensions: 1130 mm (W) × 695 mm (D) × 2210 mm (H)
Capacity: 897 L

Project:

Item #:



A high-efficiency, top-mounted heavy duty display or storage freezer suitable for both front and back of house applications. By using natural refrigerants and inverter technology the freezer achieves high performance with low energy consumption. This model has solid doors, an unlit sign and internal lighting, with customisable additional shelving, different locks, or specialised ICE storage. With L1 compliance it is engineered to serve frozen food at a standard -18°C to -21°C and is adjustable from -12°C to -26°C. It is certified under GEMS to climate class 4 and is fully tested to operate in ambient environments of up to 40°C (climate class 5). The refrigeration cartridge can be fully removed in line with best practice for safe servicing of flammable refrigerants. The cabinet includes a controller that connects to the free SKOPE-connect app to enable you to set temperatures and alerts, monitor temperatures and energy, and more. The freezer is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty

ActiveCore Technology

Natural Refrigerant


GEMS

SKOPE-connect

© 2022 SKOPE Industries Limited | We reserve the right to alter specifications without notice.

Email: skope@skope.com AUS Freephone: 1800 121 535 NZ Freephone: 0800 947 5673 skope.com

SKFT1000NS-A



Cabinet

Type	SKFT Freezer	
Finish	Stainless steel or powder-coated galvanised steel with optional colours from within the available SKOPE range	
Insulation	Type	PU foam
	Thickness (mm)	50
	Blowing Agent	Cyclo-iso pentane (C5H10/C5H12)
Doors	Type	Solid swing door
	Opening Size	Height (mm) 1570
		Width (mm) 436
Shelving	Ten adjustable height plastic-coated wire shelves 10 × half width shelf (502W × 467D)	
Lighting	Sign	n.a.
	Interior*	2 × 20 W, 1400 mm LED strip side light

Dimensions†

	External	Internal	Packed
Width (mm)	1130	1030	TBC
Depth (mm)	695	555	TBC
Height (mm)	2210 (castors)	1570	TBC
Weight (kg)	TBC		TBC
Capacity (L)	897		
Footprint (m^2)	0.79		

Ventilation (mm)

Top	300	**Sides**	Not required	**Rear**	10

Performance

Product Temperature Range (°C)	-18 to -21 (adjustable* from -12 to -26)	
Maximum Ambient Temperature (°C)	40	
Sound Level (dB(A))	Standard	62.9
	Hush Mode*	61.7

Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	2
Product Temperature Class	L1 (less than -18°C)
Total Energy Consumption	11.35 kWh/24 h
Annual Running Costs	$1243 (@ $0.30/kWh)

Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply
Cord	2 m power cord with 3-pin, 10 amp plug
Current draw (A)	5.5

Refrigeration

Controller	SCS Connect (SKOPE-connect™ compatible)			
System Type	Removable cartridge			
Cartridge Weight (kg)	47.5			
Refrigerant/Charge	R290/107 g			
Nominal Capacity (W)	1097			
Heat Rejection (W)	Average	475	Peak	600
Defrost Type	Hot gas			
Drainage	No plumbing required			

* Accessible via the free SKOPE-connect™ app.

Dimensional Tolerances

† Allow for dimensional tolerances when installing the cabinet(s).

Linear dimensions	Single cabinet	Multiple cabinets	
		At each joint	At each end wall
Less than 1 metre	±5 mm	±5 mm	+15 mm
More than 1 metre	-5 mm to +10 mm	-5 mm to +10 mm	+15 mm

SKFT1000NS-A
on the SKOPE website

© 2022 SKOPE Industries Limited | We reserve the right to alter specifications without notice.

Email: skope@skope.com AUS Freephone: 1800 121 535 NZ Freephone: 0800 947 5673 skope.com