

Two Glass Sliding Door CounterLine

Range: BackBar

SKOPE ID: CL012

Dimensions: 1585 mm (W) × 690 mm (D) × 830 mm (H)*

Capacity: 345 L

* Height with castors is adjustable from 820 to 840.

Project: _____

Item #: _____



A glass door under-counter bar fridge designed to merchandise ready-to-serve cold beverages in bars, restaurants, clubs, pubs, and cafés. Engineered to serve cold drinks at 1°C to 4°C (or adjustable up to 15°C) in ambient environments of up to 32°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The glass doors are designed for condensation protection in most environments via the double-glazed, argon-filled low-e insulated panels and heated fascia. Sliding door locks are optional. The built-in LED lights provide optimum merchandising and can be dimmed or timed to turn on and off via a free smartphone app. The fridge uses R290 natural refrigerant for ultra-low energy consumption, low heat discharge and low noise output and can be provided in remote versions. The side-mounted fully removable refrigeration cartridge (with left and right options) is front-breathing and can be removed in line with best practice for safe servicing of flammable refrigerants. The fridge includes a controller that connects to a free app to enable the user to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty




Natural Refrigerant



GEMS



SKOPE-connect



Cabinet

Type	CounterLine		
Finish	Powder-coated galvanised steel or stainless steel		
Insulation	Type	PU foam	
	Thickness (mm)	50	
	Blowing Agent	Cyclo-iso pentane (C5H10/C5H12)	
Doors	Type	Glass sliding door (double-glazed, low-e, argon-filled)	
	Opening Size	Height (mm)	538
		Width (mm)	511
Shelving	Four adjustable height powder-coated wire shelves 4 × outer shelf (547W × 530D)		
Lighting*	1 × 16 W dimmable, cool white (5500-6500K) LED strip on cabinet ceiling		

Dimensions†

	External	Internal	Packed
Width (mm)	1585	1120	TBC
Depth (mm)	690	565	TBC
Height (mm)	820 to 840 (standard castors)	545	TBC
	725 (plinth mount)		
Weight (kg)	168		TBC
Capacity (L)	345		
Footprint (m²)	1.09		

Ventilation (mm)

Top	Not required	Sides	Not required	Rear	Not required
-----	--------------	-------	--------------	------	--------------

Product Loading

Facing	330 ml can	32	600 ml bottle	28
Loading	330 ml can	256	600 ml bottle	196

* Accessible via the free SKOPE-connect™ app.

† Allow for dimensional tolerances when installing the cabinet(s).

Performance

Product Temperature Range (°C)	1 to 4 (adjustable* from 0 to 15)	
Maximum Ambient Temperature (°C)	32	
Sound Level (dB(A))	Standard	< 66
	Hush Mode*	< 62

Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	6	
Product Temperature Class	M1 (-1 to 5°C)	
Total Energy Consumption	4.13 kWh/24 h	
Annual Running Costs	\$452 (@ \$0.30/kWh)	

Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply	
Cord	1.9 power cord with 3-pin, 10 amp plug	
Current draw (A)	2.6	

Refrigeration

Controller	SCS Connect (SKOPE-connect™ compatible)		
System Type	Removable cartridge		
Cartridge Weight (kg)	24		
Refrigerant/Charge	R290/81 g		
Nominal Capacity (W)	650		
Heat Rejection (W)	Average	175	Peak 180
Defrost Type	Automatic, off-cycle		
Drainage	No plumbing required		



CL.2.GSL
on the SKOPE website