cossiga



Drainage System Options


- Plastic bottle -manual empty
- Pump to waste
- Electronic evaporator pan


- Stainless steel construction
- Four adjustable shelves
- Ticket strips on shelves
- Shelf mounted air curtains
- Under shelf and canopy LED lights
- Pull down night blind
- Forced air circulation
- Integral condenser
- Removable front grill panel
- Roll in on castors
- Climate class M1
- Hinged front door optional




Shown with optional frameless hinged acrylic front door

sold as accessory kit







CARINET DIMENSIONS & SPECIFICATIONS

CADINE	I DIME	.113101	13 Q 3	LOIL	CATIONS	,	installatio	tion guidelines, ventilation requirements and drainage options documents												
MODEL	CABINET			SHELVING	OPERATING TEMP	SHELF	BASE TRAY	DISPLAY	REFRIGERANT	FREQUENCY		ENERGY CONSUMPTION	CONNEC ELECTRICAL POWE	VOLTAGE	PACKED FOR SHIPPING					
	LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]											NZ/AUS 10 AMP						WEIGHT [KG]
DTGOR6	600	780	1860	170	4 + BASE	-1 +5	486 X 386	520 x 453	0.98	R290	50/60 HZ	1.0 / 5.5 (PTC)	14.86	3 PIN PLUG	3 PIN PLUG	220-240V	700	830	2030	180

Maximum shelf load weight 15kg spread evenly



