HOSHIZAKI


PRODUCT FEATURES


- Individual premium crescent cube with no ice bridging.
- Exceptionally hard crystal clear cubes that melt slowly.
- Durable stainless steel exterior.
- Slide in air filter at front for easy cleaning maintaining performance efficiency.
- Double-sided stainless steel evaporator for all water conditions produces more ice in less cycles.
- Flush mount to rear wall.
- Good in hard water areas.
- Snap in water tank design easy to remove for sanitization.
- Low electrical consumption.


CRESCENT ICE


CUBE SIZE:

- Low water consumption.
- 3 year parts and labour warranty on entire unit.









PRODUCT SPECIFICATION

Production Capacity	Approx. 138kg @10°C Air temp; 10°C Water
per 24hours	Approx. 126kg @21°C Air temp; 15°C Water
	Approx. 100kg @32°C Air temp; 21°C Water
Max Storage Capacity	Approx. 55kg(Bin Cont Setting Approx. 45kg)
Freeze Cycle Time	Approx. 23 Min
Ice Production Per cycle	Approx. 2.15kg/238pcs
Dimensions	762mm (W) x 712mm (D) x 992mm (H)(Height includes 152mm)
Cooling	Air
Weight Net/Gross (kg)	70/92
AC Supply Voltage	1 PHASE 220-240V 50Hz / 10Amp Plug
Amperage	Rated:4.2A Starting: 18.3A
Refrigerant Charge	R404A / 370g
	Ambient Temp.: 1- 40°C
Operating Conditions	Water Supply Temp.: 5-35°C
	Water Supply Pressure: 0.07-0.8MPa (0.7-8bar) Voltage
	Range: ± 6%

Descriptions and specifications are subject to change at any time, without notice. Illustrations for demonstration purposes.





Copyright © 2020 Hoshizaki Lancer Pty Ltd. All right reserved. E&OE Date: May 2020

TECHNICAL DRAWING