

Product Information

- Monoblock refrigeration system, for improved performance and ease of servicing
- Adjustable digital temperature controller (16° 20°C)
- Unique fan forced ducted cooling for uniformed performance throughout the entire freezer
- Protective coating on refrigeration coil to help prevent corrosion
- Environmentally friendly R290 Hydrocarbon refrigerant
- Efficient LED lighting for increased product visibility
- Stainless Steel worktop as standard, 840mm finish height. (Optional 900mm working height model available)
- 1/1GN shelf configuration with adjustable runners (2 shelves per door)
- 60mm CFC free polyurethane insulation
- Efficient and hygienic cleaning made easy with an innovative internal design
- High quality components including highly efficient compressors and EC fans
- Self-closing, lockable doors
- · Removable filter for easy cleaning
- Equipped standard with lockable castors designed for heavy-duty use
- 3 door model also available, with solid doors



Designed & Engineered in Australia to meet Australian Standards 24 Months on-site parts and labour warranty

Specifications

 Model
 AXF.UCGN.2

 W x D x H (mm)
 1360 x 700 x 840

Weight 107kg

Packed Dimensions (mm) $1390 \times 730 \times 880$

 Packed Weight
 126kg

 Net Capacity
 184 Litres

 Operation
 16°C - '20°C

 Refrigerant
 R290


 Climate Class
 4L1

 Energy Consumption
 7.2kW/b/24br

Energy Consumption 7.2kWh/24hr
Max Ambient 38°C
Total Connected Load 0.64kW

Electrical Connection 1Ø+N+E 230VAC / 50Hz

10A plug & lead



Legend

A Electrical Connection

Accessories

Shelf Kit - AXR.UCGN.SHELFKIT

1/1GN shelf with runners

