airex∋

Product Information

- Monoblock refrigeration system, for improved performance and ease of servicing
- Adjustable digital temperature controller (~16° ~20°C)
- Unique fan forced ducted cooling for uniformed performance throughout the entire freezer
- Protective coating on refrigeration coil to help prevent corrosion
- Environmentally friendly R290 Hydrocarbon refrigerant
- Efficient LED lighting for increased product visibility
- Stainless Steel worktop as standard, 840mm finish height. (Optional 900mm working height model available)
- 1/IGN shelf configuration with adjustable runners (2 shelves per door)
- 60mm CFC free polyurethane insulation
- Efficient and hygienic cleaning made easy with an innovative internal design
- High quality components including highly efficient compressors and EC fans
- Self-closing, lockable doors
- Removable filter for easy cleaning
- Equipped standard with lockable castors designed for heavy-duty use
- 2 door model also available, with solid doors

Designed & Engineered in Australia to meet Australian Standards 24 Months on-site parts and labour warranty

Specifications


Model	AXF.UCGN.3
W x D x H (mm)	1795 x 700 x 840
Weight	128kg
Packed Dimensions (mm)	1825 x 730 x 880
Packed Weight	152kg
Net Capacity	276 Litres
Operation	-16°C20°C
Refrigerant	R290
Climate Class	4L1
Energy Consumption	8.23kWh/24hr
Max Ambient	38°C
Total Connected Load	0.65kW
Electrical Connection	1Ø+N+E 230VAC / 50Hz 10A plug & lead


Legend

A Electrical Connection

Accessories

Shelf Kit -1/1GN shelf with runners AXR.UCGN.SHELFKIT









Revision: B - 05/12/2024 - 02

Due to continuous product research and development, the information contained herein is subject to change without notice.