

Product Information

- Monoblock refrigeration system, for improved performance and ease of servicing
- Adjustable digital temperature controller (0°C 6°C)
- · Vertically integrated ducted cooling throughout the entire refrigerator
- Protective coating on refrigeration coil to help prevent corrosion
- Environmentally friendly R290 Hydrocarbon refrigerant
- · Efficient LED lighting for increased product visibility
- Five adjustable 2/IGN shelves supplied per door to maximise storage capacity
- Double glazed heated glass door for exceptional display and minimal condensation
- 80mm CFC free polyurethane insulation
- Efficient and hygienic cleaning made easy with an innovative internal design
- High quality components including highly efficient compressors and EC fans
- · Self-closing, lockable doors
- · Removable filter for easy cleaning
- · Equipped standard with lockable castors designed for heavy-duty use
- 2 door model available, with glass or solid doors

Designed & Engineered in Australia to meet Australian Standards 24 Months on-site parts and labour warranty



Specifications

 Model
 AXR.URGN.1G

 W x D x H (mm)
 700 x 850 x 1990

Weight 138kg

Packed Dimensions (mm) $730 \times 875 \times 2040$

 $\begin{tabular}{lll} \textbf{Packed Weight} & 145 kg \\ \textbf{Net Capacity} & 369 \ Litres \\ \textbf{Operation} & 0^{\circ}\text{C} - 6^{\circ}\text{C} \\ \textbf{Refrigerant} & R290 \\ \textbf{Climate Class} & 4M1 \\ \end{tabular}$

Energy Consumption 4.19kWh/24hr

Max Ambient40°CTotal Connected Load0.59kW

Electrical Connection 1Ø+N+E 230VAC / 50Hz

10A plug & lea

Accessories

Shelf Kit - AXR.URGN.SHELFKIT

2/1GN shelf with runners

Tray runners to suit AXR.URGN.SHELFKIT.BAKERY 600x400 travs







