

# BME ACTIVECORE™

## Glass Door Chiller

### Display / Bottom Mount - Limited options

A new glass door chiller combining SKOPE's revolutionary new ActiveCore technology with a modern frameless aesthetic design. These models provide market leading energy savings along with new features to deliver optimal performance, efficiency and reliability.

#### Options

Available in 1, 2 and 3 door models  
Additional shelves  
Illuminated sign panel

#### SIGNIFICANT ENERGY SAVINGS

Uses 35% less energy than the previous B1200G-2 model, saving more than \$266 per year\*

Significantly reduced noise and improved quality, for quieter operation

Patented easy to install shelf clip and numbered shelf support strip, reduces set up time and enables finer adjustments

A frameless glass door design with aluminium trim

Redesigned kick panel for branding opportunities and easy access to filter for maintenance



Available in white only

Fitted with lock tabs for extra security

Optimal airflow and cooling performance reduces temperature variations and energy consumption

Split shelving system for improved product presentation

Premium energy efficient glass using new low-emissivity coating technology, equivalent to double Low-E performance. An invisible finish ensures maximum visual clarity\*\*

Ergonomically designed, brushed stainless steel handles

New slotted back panel design allows chilled airflow to be pushed directly on the product

Updated controller with manual light switch

Revolutionary removable ActiveCore refrigeration system



Easy to remove ActiveCore Cartridge System inside



**Warranty**  
2 year protection




**High Energy Efficiency**




ActiveCore™

# Specifications

## BME ActiveCore™ Display / Bottom Mount





Integral top view




Integral front elevation

### BME600-A- GLASS DOOR

Model	Integral/Remote	Chiller/Freezer	Colour	
<b>BME600-A</b>	Integral	Chiller	White	<b>Gross Volume</b> 584 litres <b>Total Shelf Area</b> 1.62m <sup>2</sup> (inc. floor) <b>Floor Area</b> 0.63m <sup>2</sup> (inc. 50mm stand-off) <b>Weight</b> 185 kg
	External (mm)	Internal (mm)		  <b>BME600-A</b> 1 DOOR
<b>Height</b>	2005	1454		
<b>Width</b>	740	640		
<b>Depth***</b>	795	602		
	<ul style="list-style-type: none"> <li>• 4.35 MEPS (kWhr/24hr/m<sup>2</sup>)</li> <li>• Maximum height 2195mm with optional sign panel fitted</li> <li>• +1°C to +4°C in 43°C ambient</li> <li>• 3.05 TEC (kWh/24h)</li> </ul>			





Integral top view




Integral front elevation

### BME1200-A - GLASS DOOR

Model	Integral/Remote	Chiller/Freezer	Colour	
<b>BME1200-A</b>	Integral	Chiller	White	<b>Gross Volume</b> 1079 litres <b>Total Shelf Area</b> 3.00m <sup>2</sup> (inc. floor) <b>Floor Area</b> 1.08m <sup>2</sup> (inc. 50mm stand-off) <b>Weight</b> 245 kg
	External (mm)	Internal (mm)		  <b>BME1200-A</b> 2 DOOR
<b>Height</b>	2005	1454		
<b>Width</b>	1280	1180		
<b>Depth***</b>	795	602		
	<ul style="list-style-type: none"> <li>• 3.86 MEPS (kWhr/24hr/m<sup>2</sup>)</li> <li>• Maximum height 2195mm with optional sign panel fitted</li> <li>• +1°C to +4°C in 43°C ambient</li> <li>• 4.55 TEC (kWh/24h)</li> </ul>			




Integral top view



Integral front elevation

### BME1500-A - GLASS DOOR

Model	Integral/Remote	Chiller/Freezer	Colour	
<b>BME1500-A</b>	Integral	Chiller	White	<b>Gross Volume</b> 1433 litres <b>Total Shelf Area</b> 3.94m <sup>2</sup> (inc. floor) <b>Floor Area</b> 1.34m <sup>2</sup> (inc. 50mm stand-off) <b>Weight</b> 330 kg
	External (mm)	Internal (mm)		  <b>BME1500-A</b> 3 DOOR
<b>Height</b>	2005	1454		
<b>Width</b>	1640	1540		
<b>Depth***</b>	795	602		
	<ul style="list-style-type: none"> <li>• TBA MEPS (kWhr/24hr/m<sup>2</sup>)</li> <li>• Maximum height 2195mm with optional sign panel fitted</li> <li>• +1°C to +4°C in 43°C ambient</li> <li>• TBA TEC (kWh/24h)</li> </ul>			

Height includes castors

\*Based on 30 cents per kW. Calculated using 4.55 kWh/24h(TEC) no illuminated sign panel

\*\*For tropical installations please speak to a SKOPE representative

\*\*\*Total depth includes removable 50mm handles, and excludes 50mm retractable stand-off