

### Product Information

- This unit is designed to be mounted under a custom made stainless steel bench (manufactured & fitted by others)
- Wet or dry operation (temperature varies greatly when run dry, should not be left unattended for long periods of time)
- Temperature regulation via digital control, designed to hold product between 65°C - 90°C.
- Air insulated, double skinned tank for energy efficient heating
- Robust 304 grade stainless steel construction
- Manual fill and manual empty, valve operated waste
- 1/1 GN sized well, fits pans up to 150mm deep (sold separately). Pan dividers not supplied
- **12-month parts and labour warranty**



### Specifications

<b>Model</b>	CH.BM.U.3
<b>W x D x H (mm)</b>	1100 x 610 x 283
<b>Total Connected Load</b>	2.25kW
<b>Electrical Connection</b>	1Ø+N+E 240VAC / 50Hz (Onsite connection)
<b>Water Connection</b>	G 1/2" BSP
<b>Waste Connection</b>	1 1/4" BSP

### Optional Extras

#### Radius Well

Add **R** to code after the **U** CH.BM.UR.3

Note: Radius Well must be nominated at time of order

### Accessories

<b>Large Pan Dividers</b> (To suit large GN pans)	CA.PXL
<b>Cross Pan Dividers</b> (To suit smaller GN pans)	CA.PXS

### Legend

- A** Electrical Connection
- B** Water Connection
- C** Waste Connection

