

### Product Information:

- This unit is designed to be mounted under a custom made bench top of your choice (manufactured & fitted by others)
- Wet or dry operation (temperature varies greatly when run dry, should not be left unattended for long periods of time)
- Temperature regulation via digital control, designed to hold product between 65°C - 90°C.
- Air insulated, double skinned tank for energy efficient heating
- Hot cupboard equipped with a fan forced heating system
- Independent controls for baine marie, hot cupboard, and gantry
- Gantry fitted with 10mm thick toughened glass and overhead Quartz IR heat lamps with adjustable temperature
- Gantry height adjustable at installation for bench top thickness
- Robust 304 grade stainless steel construction
- Manual fill and manual empty, valve operated waste
- 1/1 GN sized well, fits pans up to 150mm deep (sold separately). Pans are recessed to minimise water condensation on surrounding bench top
- Additional combinations and painted black centre section available (P.O.A), contact your Stoddart representative for more information
- **Made to Order**
- **12-month parts and labour warranty**



### Specifications

<b>Model</b>	CH.BMHC.U.GSF.4
<b>W x D x H (mm)</b>	1543 x 830 x 1260
<b>Total Connected Load</b>	5.7kW
<b>Electrical Connection</b>	3Ø+N+E 400VAC / 50Hz (Onsite connection)
<b>Water Connection</b>	G 1/2" BSP
<b>Waste Connection</b>	1 1/4" BSP

### Optional Extras

<b>Radius Well</b>	
Add <b>R</b> to code after the <b>U</b>	CH.BMHC.UR.GSF.4

#### Left Hand Controls

Add **.L** after the **U** or **UR** in the product code to specify left hand controls  
CH.BMHC.UR.L.GSF.4

### Legend

- A** Electrical Connection
- B** Water Connection
- C** Waste Connection

