

“Connect & use” glasswasher to suit racks 400x400mm & 17”x14”



Product Advantages:

- **Easy-to-use** electronic controls with 2 cycles - 60 & 120 seconds
- **Re-circulating & low 2.0 litre rinse volume** glasswasher
- Digital temperature gauges
- Suitable for all glass, cup and light duty washing applications
- Designed to suit racks 400x400mm & 17”x14”
- **Double skinned door** for strength and durability
- Polypropylene wash & rinse arm with **patented WIDE ANGLE FAN** nozzle to maximise wash & rinse performance
- Wash pump inlet strainer to ensure machine reliability
- “**Connect & use**”- fill and drain hoses, pump-out drain, chemical dispensers and power lead / plug included for quick and easy installation
- Standard with 150mm stainless steel adjustable legs
- Includes 1 x 17”x14” glass rack,
- Back flow prevention device as standard to meet Watermark Approval and ATS 5200.101
- **NOT SUITABLE FOR USE WITH REVERSE OSMOSIS SYSTEMS**
- **MADE IN GERMANY**

Technical Data

| | |
|--|--------------------------------|
| flexible drain hose 1000mm | Pump-out drain standard |
| fresh water connection: pressure hose 1000mm | Connection size: 3/4" BSP |
| flow pressure | 80-600kPa |
| incoming water temperature | 55-65°C |
| power cord | 15amp single phase plug & lead |
| hose for detergent hose for rinse aid | Included |
| wash tank temperature | 55-60°C |
| rinse water temperature (booster tank) | Minimum 82°C |
| low temp cut-out (thermostop) activated | Yes |
| cycle times | 60 sec. 120 sec. |
| water consumption | 2.0litres |
| tank capacity | 10litres |
| tank heating | 1.8kW |
| power supply | 240/50/1 - 15amp |
| booster loading | 1.9kW |
| total loading | 2.1kW |
| pump capacity | 180watts |
| loading height | 308mm |

Water hardness should not exceed 3°dH, if higher we recommend using a water softener.

If mineral content is high a demineraliser may be advisable.

