



TECHNICAL DATA

Cycle times (*)	90 / 180 sec.
Water consumption	2.8I/cycle
Tank capacity	10.61
Tank heating	0.8kW
Power supply	240/50/1 (standard)
Booster loading	
Standard	2.1kW (Interlocked)
Alternative	6.2kW
Total loading	
Standard	2.8kW 15amp
Alternative	7.7kW 415/50/3N
Wash pump	0.6 kW
Rack size	500 x 500mm
Loading height	425mm
Noise level	60.5 dB (A)
Weight (gross / net)	70 / 60kg

CONNECTIONS

① Drain hose	2,000 mm ID20/ OD25
② Supply hose	2,000 mm R 3/4"
Flow pressure	0.5 (0.8 with softener) - 10 bar
Max. supply water temperature	60 °C
Required flow rate	5 l/min
3 Power cord	2,000 mm
Supply hose for	
Detergent	2,500 mm
⑤ Rinse aid	2,500 mm

- * Thermostop guarantees required rinse temperatures. The actual cycle time extends accordingly if the machine is connected to cold water or run on single phase
- * For machine protection water hardness should not exceed 3°dH. If higher we recommend using a water softener - ask your Hobart representative for assistance.

PRODUCT ADVANTAGES

- HIGH VOLUME undercounter dish and glass washer
- LOW VOLUME (10.6litre) single sheet deep drawn wash tank no welds
- EFFICIENT & GUARANTEED 2.8 litres / cycle water consumption rinse pump included as standard
- Electronic control with temperature indication
- 2 CYCLES: 90 / 180 secs Nominal capacity up to 30 racks/h
- HEAT AND NOISE INSULATED double walled housing and heat insulated front door
- Smooth opening counter balanced door
- Removable tank strainer, coarse filter and pump suction casing to maximise wash results and reliability
- Integrated SELF CLEANING on drain out
- Top and bottom rotating wash and rinse arms
- Ready to install equipped with: fill/drain hoses, electrical cable & plug (15amp 240V), detergent & rinse aid dispensers, rinse pump, drain pump, back flow preventer (Watermark approved), adjustable front feet for levelling and castor rear feet for ease of moving for cleaning under
- Supplied with 1 off 500 x 500mm plate rack, flat rack and single cutlery container
- 240 / 50 / 1 15amp (Optional 415/50/3 additional cost)
- MADE IN GERMANY

DIMENSIONAL DRAWING

* Plus adjustable feet / rear castors

