PLATINUM SERIES GAS FILTER DRAWER SYSTEMS

FDAGP455C


The Platinum series gas fryer are high efficiency fryers that deliver optimum performance while using minimal gas. Platinum fryers are supplied standard with Anets Platinum burner technology incorporating a highly efficient Energy Star® rated atmospheric burner reaching up to 70% thermal efficiency and lower flue temperatures. The patented burner also has a daily self-cleaning cycle, keeping burners tuned to operate in the most energy efficient manner.


Product Information:

- Platinum series gas filter drawer systems come with the AGP55 fryers banked together
- Digital or computer controlled 3 fryer filter drawer system
- 4 x 102mm deep burners per tank
- Computer control with melt cycle and boil out modes.
 Complete with backup solidstate controller which can be switched on should the computer control fail.
- Easy two step filtering
- 30 litre per minute filter pump for fast refill times
- Self aligning filter connection for effortless hookup
- Rear oil return for bottom cleaning
- Filter pan is stainless with rear wheels for easy handling
- Filter pan lid is self storing and out of the way
- All filtration systems come standard on adjustable height castors, and with Washdown/discharge hose, Box of 50 envelope papers, Starter sample pack of filter powder, Lids, Clean out rod and brush
- Cooking capacity of approximately 160kg of frozen 10mm fries / 192kg of frozen french cut fries per hour per tank


OPTIONAL EXTRAS:

- Basket lifters
- Digital Control
- Heat tape





<u>___</u>







TECHNICAL DATA:

ANETS

Dimensions (W x D x H):	1191 x 876 x 1172	
Total Weight:	285Kg	
Cooking Area (W x D x H):	356 x 356 x 127mm (x3)	
Oil Capacity:	19-21 Litres per tank	
GAS DETAILS	Natural Gas (NG)	Universal LP Gas (ULPG)
GAS DETAILS Minimum Supply Pressure		
	Gas (NG)	LP Gas (ULPG)

3/4" BSP connection

Legend:

- A Electrical Connection
- B Gas Connection
- C Solid State Controls
- D Computer Control Panel
- E Basket Lifter (Optional)
- F Digital Control Panel (Optional)

240 Volt 10Amp connection required to run filter system & control board.

NOTE: It is the responsibility of the installing gas plumber to ensure correct supply and connection sustaining appropriate pressure when all appliances are full on





Due to continuous product research and development, the information contained herein is subject to change without notice. Revision: B - 2/8/2024 - 02

www.stoddart.com.au www.stoddart.co.nz