

LINCOLN

1240mm height






STANDARD FEATURES

- FrameFree canopy that maximises fully the visibility of displayed food
- Four food display levels: three shelves plus bottom trays
- Chrome wire shelving system that is height adjustable in 25mm increments and interchangeable between horizontal and tilted positions
- **CrumbCatch** feature in bottom trays that collects falling crumbs and food
- High quality European refrigeration components
- Designed to operate at 3 5°C in room environments up to 32°C
- > Fan forced air flow for even temperature distribution
- **i-frost** intelligent defrost control that minimises time in defrost to better maintain consistent food temperature
- > Refrigeration optimised to provide a high humidity environment that maintains food quality for longer
- > **DuraCoat** system providing a protective coating over the refrigeration coil to prevent food acid corrosion
- > **SureVap** self-evaporating system for condensate—no drain required
- > Condenser air vented through base—no unsightly vents
- **SlimLED** under-shelf LED strip lighting with 12V safety
- > Rear sliding, double-glazed doors on friction-free, low wear tracks (doors removable for cleaning)
- > Mounted on swivel and lockable castors allowing easy movement of cabinet

SIDE VIEW



LINCOLN: **CHILLED**

The Lincoln cabinet adds a designer look to any food service environment. The curved glass front of the elegant Lincoln cabinet gives visual impact and provides an unobstructed view of the displayed food.

4°C operating temperature

For Factory Options refer to page 46 For Cabinet Accessories refer to page 56

Model	LC6	LC9	LC12	LC15	LC18	LC24
Length	600mm	900mm	1200mm	1530mm	1770mm	2370mm
Depth*	640mm	640mm	640mm	640mm	640mm	640mm
Height	1240mm	1240mm	1240mm	1240mm	1240mm	1240mm
Available Display Area	0.84m²	1.34m²	1.83m²	2.4m²	2.7m²	3.7m ²
Power Connection	10A Plug					

^{*}Add extra 15mm for protruding control panel and switches




STANDARD FEATURES

- FrameFree canopy that maximises fully the visibility of displayed food
- > Four shelf levels
- > Chrome wire shelving system that is height adjustable in 25mm increments and interchangeable between horizontal and tilted positions
- > High quality European heating and control components
- > Thermostatically controlled to operate at a temperature between 30 - 95°C
- Fan forced air flow for even heat distribution
- Rapid response element for better temperature control
- > **SlimLED** under-shelf LED strip lighting with 12V safety
- > Rear sliding doors on friction-free, low wear tracks (doors removable for cleaning)
- > Mounted on swivel and lockable castors allowing easy movement of cabinet

For Factory Options refer to page 46 For Cabinet Accessories refer to page 56

SIDE VIEW



LINCOLN: **HEATED**

This designer cabinet allows great viewing of heated food offerings, simply drawing the customer in to encourage food purchase.

up to 95°C operating temperature

Model	LH6	LH9	LH12	LH15
Length	600mm	900mm	1200mm	1530mm
Depth*	640mm	640mm	640mm	640mm
Height	1240mm	1240mm	1240mm	1240mm
Available Display Area	0.85m ²	1.4m²	1.9m²	2.4m²
Power Connection	10A Plug	10A Plug	10A Plug	20A Plug

^{*}Add extra 15mm for protruding control panel and switches




STANDARD FEATURES

- > FrameFree canopy that maximises fully the visibility of displayed food
- > Four food display levels: three shelves plus base
- > Chrome wire shelving system that is height adjustable in 25mm increments and interchangeable between horizontal and tilted positions
- **SlimLED** under-shelf LED strip lighting with 12V safety
- > Top venting to allow heat dissipation
- Rear sliding doors on friction-free, low wear tracks (doors removable for cleaning)
- Mounted on swivel and lockable castors allowing easy movement of cabinet

For Factory Options refer to page 46 For Cabinet Accessories refer to page 56

SIDE VIEW



LINCOLN: **AMBIENT**

This cabinet offers class to any ambient food offering. With its minimalist and stylish look, product stands out and tempts the customer.

Model	LA6	LA9	LA12	LA15	LA18	LA24
Length	600mm	900mm	1200mm	1530mm	1770mm	2370mm
Depth*	640mm	640mm	640mm	640mm	640mm	640mm
Height	1240mm	1240mm	1240mm	1240mm	1240mm	1240mm
Available Display Area	0.84m ²	1.34m²	1.83m²	2.4m²	2.7m²	3.7m²
Power Connection	10A Plug	10A Plug	10A Plug	10A Plug	10A Plug	10A Plug

^{*}Add extra 15mm for protruding control panel and switches