"Twin size"



Product Advantages:


- Significantly **less manual pre-cleaning and second runs** by intensiv wash cycle with **steam injection** and **direct injection of detergent**
- Extra capacity by side wash: e.g. up to 8 GN-trays 1/1, 5 EN2 container ...
- Ease of operation with single button operation, colour coded status and remaining cycle time indication
- Easy to clean and hygienic safety by self cleaning, hygiene cycle and rounded edges in the wash chamber
- Double walled housing for low noise level and energy efficiency
- Useable inside dimensions w x d x h: 1110 x 773 x 825 mm
- No clogging of wash nozzles by strainer sensor control
- Completely equipped with rinse pressure pump, drain pump and chemical dispensers
- Integrated prewash by GENIUS-X² fine filter system: achieving better wash results due to permanent filtration of wash water saving energy and detergent

Drawing shows optional steam heat recovery 1980 1980 1088 390 1088 1088 1088

** Door opening can be limitted to 2200mm

Technical Data

① flexible drain hose	24mm inner /
2000 mm	28mm outer diam.
2 fresh water connection:	
pressure hose	
1500 mm	R 3/4" inside
flow pressure	0,5 - 10 bar
	max. 60°C
③ power cord	1800 mm
4 chemical	
suction hoses	2500 mm each
Cycle times	150 sec.
	280 sec.
	420 sec.
	endless
Rinse water consumption	14 l/ rack
Tank capacity	130 I
Tank heating	6 kW
Booster loading	18 kW
Voltage	400 / 50 / 3 / N
Total loading	21.3 kW
	3 x 50 A
Pump capacity	2 x 2.7 kW
	2 x 1150 l/min.
Noise level	67 dB(A)
Weight	~305 kg



 \pm 15 mm adjustable feet For transport the depth can be reduced to 870mm

Water hardness should not exceed 3°dH, if higher we recommend using a water softener.

If mineral content is high a demineraliser may be advisable.