

Copyright © 2018 SKOPE Industries Limited

GENERAL SPECIFICATIONS		
Temperature range	1°C to 4°C (adjustable up to 15°C)	
Climate class	5 (Tested at 43°C)	
Doors	Lockable, self-closing, reversible, double glazed, single Low-E, argon filled, toughened safety glass swing doors (hinged LH, RH)	
Internal Volume	980 litres	
Interior lighting	2 × 15W (1400mm) LED module strip side lights	
Power supply	220-240 Volts a.c. 50 Hz, single phase supply. Supplied with 10 Amp 3-Pin plug	
Current draw	3.0 Amps (includes unit 2.6 Amps)	
Refrigeration system	Removable ActiveCore top mount refrigeration unit (UTHCNI-0010) (compressor: Wanbao FN90M)	
Refrigerant	R290 / 99g	
Nominal capacity	740 Watts	
Controller	Wellington Drive SCS Connect	
Connectivity interface:	Bluetooth	
Drainage	No plumbing required	
Weight	225 kg	

INDIVIDUAL SPECIFICATIONS			
Model ID	TME1000N-A	TME1000N-AC	
SKOPE ID	SM10GYN	SM10BYN	
Sign	Sign replacement panel	400mm high illuminated sign	
Sign lighting	n.a.	1 × 12W (1060mm) LED module strip sign light	
Shelves	5 × adjustable height wire shelves: 1015mm wide × 470mm deep	10 × adjustable height wire shelves: 500mm wide × 470mm deep	

SKOPE Industries Limited reserve the right to alter specifications without notice.



PSS0518 Rev. 1.0 Jul. 2018

4 × 100mm high swivel castors (front lockable)



Email: skope@skope.co.nz, Website: www.skope.com